

BUNKER

Small-Size Tracked Mobile Robot Unmanned Ground Vehicle



IP67 Solids Protection/ Waterproof



115mm Obstacle Surmounting Capacity



Better Climb Capability



High Payload Capability







Capable of Deeply Wading Water



Applications:

Waterway Surveying and Mapping

Mineral Exploration

Pipeline Inspection

Security Inspection

Unconventional Photographing

Special Transportation







Tech Specification	S
Dimensions	660*584*281mm
Height	65.5mm
Track width	100mm
Weight	54.8kg
Maximum Payload	35kg
Max Speed	0~1.5m/s
Climbing Ability	30° (No payload)
Minimum Turning Radius	0m (In-situ Rotation)
Obstacle Surmounting Capacity	115mm
Operating Temperature	-20°C~60°C
Battery	24V 30Ah Lithium Battery
Charging Time	3-4h
External Power Supply	24V/15A
Charger	AC220V Charger
Power Drive	Left and Right Independent Drive Track-type Differential Steering
Motor	250W*2 (Brushed DC Motor)
Rated Torque	17N·m
Code Wheel	1024 Line Magnetic Encoder
Protection Level	IP67
Communication Interface	CAN

Add: A1-305, 3rd Floor, Building 1, Private Enterprise Technology Park, No. 65, Lishan Road, Pingshan Community, Taoyuan Street, Nanshan District, Shenzhen, Guangdong Province, China